





## Fichier de configuration - Routeur

```
interface GigabitEthernet0/0/0
 ip address 10.0.1.1 255.255.255.252
 ip helper-address 172.16.0.1
 negotiation auto
!
interface GigabitEthernet0/0/0.1
 encapsulation dot1Q 1 native
 ip address 192.168.0.254 255.255.255.0
!
interface GigabitEthernet0/0/0.2
 encapsulation dot1Q 2
 ip address 172.16.1.254 255.255.255.0
 ip helper-address 172.16.0.1
!
interface GigabitEthernet0/0/0.3
!
interface GigabitEthernet0/0/0.100
 encapsulation dot1Q 100
 ip address 172.16.0.254 255.255.255.0
 ip helper-address 172.16.0.1
!
interface GigabitEthernet0/0/1
 ip address 10.0.0.1 255.255.255.252
 negotiation auto
!
interface GigabitEthernet0
 vrf forwarding Mgmt-intf
 no ip address
 shutdown
 negotiation auto
!
router rip
 version 2
 network 10.0.0.0
 network 172.16.0.0
 network 192.168.0.0
!
ip forward-protocol nd
ip http server
ip http authentication local
ip http secure-server
ip tftp source-interface GigabitEthernet0
ip route 0.0.0.0 0.0.0.0 10.0.0.2
!
```

## Fichier de configuration - Routeur

```
ip ssh version 2
!
!
!
!
!
control-plane
!
!
line con 0
  transport input none
  stopbits 1
line aux 0
  stopbits 1
line vty 0 4
  login local
  transport input ssh
line vty 5 15
  login local
  transport input ssh
!
wsma agent exec
!
wsma agent config
!
wsma agent fileysys
!
wsma agent notify
!
!
end

ROUTER_ASSUR#
```