

Fichier de configuration - Switch

```
SWITCH_ASSUR#sh run
Building configuration...

Current configuration : 2440 bytes
!
! Last configuration change at 18:24:51 UTC Sat Mar 11 2000 by admin
! NVRAM config last updated at 14:41:06 UTC Fri Mar 10 2000 by admin
!
version 15.2
no service pad
service timestamps debug datetime msec
service timestamps log datetime msec
no service password-encryption
!
hostname SWITCH_ASSUR
!
boot-start-marker
boot-end-marker
!
enable secret 5 $1$pZ.c$3JH031cT2FQ6SuSqe4358/
!
username admin secret 5 $1$Rod8$8TgIaLLCSLBekM3uvTPAt1
no aaa new-model
switch 1 provision ws-c2960x-24ts-l
!
!
!
!
!
!
!
ip domain-name assur-mer.fr
!
!
!
!
!
!
!
spanning-tree mode rapid-pvst
spanning-tree extend system-id
!
!
!
!
vlan internal allocation policy ascending
```

Fichier de configuration - Switch

```
interface FastEthernet0
  no ip address
!
interface GigabitEthernet1/0/1
  switchport access vlan 100
!
interface GigabitEthernet1/0/2
  switchport access vlan 100
!
interface GigabitEthernet1/0/3
!
interface GigabitEthernet1/0/4
!
interface GigabitEthernet1/0/5
!
interface GigabitEthernet1/0/6
!
interface GigabitEthernet1/0/7
!
interface GigabitEthernet1/0/8
!
interface GigabitEthernet1/0/9
!
interface GigabitEthernet1/0/10
!
interface GigabitEthernet1/0/11
!
interface GigabitEthernet1/0/12
!
interface GigabitEthernet1/0/13
  switchport access vlan 2
!
interface GigabitEthernet1/0/14
  switchport access vlan 2
!
interface GigabitEthernet1/0/15
  switchport access vlan 2
```

Fichier de configuration - Switch

```
interface GigabitEthernet1/0/16
!
interface GigabitEthernet1/0/17
!
interface GigabitEthernet1/0/18
!
interface GigabitEthernet1/0/19
!
interface GigabitEthernet1/0/20
  switchport access vlan 2
  switchport mode access
!
interface GigabitEthernet1/0/21
  switchport trunk allowed vlan 1,10,20,30,40,90,100
  switchport mode trunk
  shutdown
!
interface GigabitEthernet1/0/22
  switchport trunk allowed vlan 1,2,10,20,30,40,90,100
  switchport mode trunk
!
interface GigabitEthernet1/0/23
  switchport trunk allowed vlan 1,2,10,20,30,40,90,100
  switchport mode trunk
!
interface GigabitEthernet1/0/24
  switchport trunk allowed vlan 1,2,10,20,30,40,90,100
  switchport mode trunk
!
interface GigabitEthernet1/0/25
!
interface GigabitEthernet1/0/26
!
interface GigabitEthernet1/0/27
!
interface GigabitEthernet1/0/28
!
interface Vlan1
  ip address 192.168.0.100 255.255.255.0
!
ip default-gateway 192.168.0.254
!
ip http server
ip http secure-server
ip ssh version 2
```

Fichier de configuration - Switch

```
line con 0
line vty 0 4
  login local
  transport input ssh
line vty 5 15
  login local
  transport input ssh
!
!
end
SWITCH_ASSUR#
```